

The longtable package*

David Carlisle†

2025-10-13

This file is maintained by the L^AT_EX Project team.
Bug reports can be opened (category `tools`) at
<https://latex-project.org/bugs.html>.

Abstract

This package defines the `longtable` environment, a multi-page version of `tabular`.

List of Tables

1	An optional table caption (used in the list of tables)	2
2	A floating table	4
3	A difficult <code>\multicolumn</code> combination: pass 1	6
4	A difficult <code>\multicolumn</code> combination: pass 2	6
5	A difficult <code>\multicolumn</code> combination: pass 3	6
6	A difficult <code>\multicolumn</code> combination: pass 4	6
7	A summary of <code>longtable</code> commands	9

1 Introduction

`longtable` (*env.*) The `longtable` package defines a new environment, `longtable`, which has most of the features of the `tabular` environment, but produces tables which may be broken by T_EX's standard page-breaking algorithm. It also shares some features with the `table` environment. In particular it uses by default the same counter, `table`, and has a similar `\caption` command. Also, the standard `\listoftables` command lists tables produced by either the `table` or `longtable` environments.

The following example uses most of the features of the `longtable` environment. An edited listing of the input for this example appears in Section 9.

Note: Various parts of the following table will **not** line up correctly until this document has been run through L^AT_EX several times. This is a characteristic feature of this package, as described below.

*This file has version number v4.24, last revised 2025-10-13.

†The new algorithm for aligning 'chunks' of a table used in version 4 of this package was devised, coded and documented by David Kastrup.

Table 1: (continued)

* This part appears at the top of every other page *	
* First	* Second *
Some lines may take up a lot of space, like this:	This last column is a “p” column so this “row” of the table can take up several lines. Note however that T _E X will never break a page within such a row. Page breaks only occur between rows of the table or at <code>\hline</code> commands.
* Lots of lines	like this. *
* Lots of lines	like this. *
* Lots of lines	like this. *
* Lots of lines	like this. *
* Lots of lines	like this. *
* Lots of lines	like this. *
* Lots of lines	like this. *
* Lots ¹ of lines	like this. *
* Lots of lines	like this ² *
* Lots of lines	like this. *
* Lots of lines	like this. *
* These lines will	appear *
* in place of the	usual foot *
* at the end	of the table *

2 Chunk Size

`LTchunksize` In order to T_EX multi-page tables, it is necessary to break up the table into smaller chunks, so that T_EX does not have to keep everything in memory at one time. By default `longtable` uses 20 rows per chunk, but this can be set by the user, with e.g., `\setcounter{LTchunksize}{10}`.³ These chunks do not affect page breaking, thus if you are using a T_EX with a lot of memory, you can set `LTchunksize` to be several pages of the table. T_EX will run faster with a large `LTchunksize`.

¹This is a footnote.

²`longtable` takes special precautions, so that footnotes may also be used in ‘p’ columns.

³You can also use the plain T_EX syntax `\LTchunksize=10`.

A	tabular	environment
within	a floating	table

Table 2: A floating table

However, if necessary, `longtable` can work with `LTchunksize` set to 1, in which case the memory taken up is negligible. Note that if you use the commands for setting the table head or foot (see below), the `LTchunksize` must be at least as large as the number of rows in each of the head or foot sections.

This document specifies `\setcounter{LTchunksize}{200}`. If you look at the previous table, after the *first* run of \LaTeX you will see that various parts of the table do not line up. \LaTeX will also have printed a warning that the column widths had changed. `longtable` writes information onto the `.aux` file, so that it can line up the different chunks. Prior to version 4 of this package, this information was not used unless a `\setlongtables` command was issued, however, now the information is always used, via a new algorithm,⁴ and so `\setlongtables` is no longer needed. It is defined (but does nothing) for the benefit of old documents that use it.

3 Counter and Caption Types

As mentioned in the introduction `longtable` uses and updates by default the `table` counter, the `\caption` command creates a table caption which is added to the list of tables. Packages like `lcaption` added more flexibility here by adding the command `\LTcapttype` which allowed to change the type, e.g. to a listing. Starting with version 4.21 `longtable` supports this command directly. By redefining this command it is possible to change the counter and caption type. After `\renewcommand\LTcapttype{<counter>}` `longtable` will update the counter `<counter>`, use `\fnum<counter>` in the caption (which typically will make use of `\<counter>name` and `\the<counter>`), and write content line entries into the file with the extension stored in the command `\ext<counter>`. When `hyperref` is loaded the name of the anchor will use `<counter>` too. Packages or documents that change `\LTcapttype` to some nonstandard value must ensure that the counter `<counter>` and the commands `\fnum<counter>` and `\ext<counter>` exist and do not error. If `\LTcapttype` is empty no counter is advanced and `\<counter>name` in the caption is suppressed.

4 Captions and Headings

At the start of the table one may specify lines which are to appear at the top of every page (under the headline, but before the other lines of the table). The lines are entered as normal, but the last `\` command is replaced by a `\endhead` command. If the first page should have a different heading, then this should be entered in the same way, and terminated with the `\endfirsthead` command. The `LTchunksize` should be at least as large as the number of rows in the heading.

There are also `\endfoot` and `\endlastfoot` commands which are used in the same way as `\endhead` and `\endfirsthead`.

⁴Due to David Kastrup.

way (at the *start* of the table) to specify rows (or an `\hline`) to appear at the bottom of each page. In certain situations, you may want to place lines which logically belong in the table body at the end of the `firsthead`, or the beginning of the `lastfoot`. This helps to control which lines appear on the first and last page of the table.

`\caption` The `\caption{...}` command is essentially equivalent to `\multicolumn{n}{c}{\parbox{LTcapwidth}{...}}` where `n` is the number of columns of the table. You may set the width of the caption with a command such as `\setlength{LTcapwidth}{2in}` in the preamble of your document. The default is 4in. `\caption` also writes the information to produce an entry in the list of tables. As with the `\caption` command in the `figure` and `table` environments, an optional argument specifies the text to appear in the list of tables if this is different from the text to appear in the caption. Thus the caption for table 1 was specified as `\caption[An optional table caption (used in the list of tables)]{A long table\label{long}}`.

You may wish the caption on later pages to be different to that on the first page. In this case put the `\caption` command in the first heading, and put a subsidiary caption in a `\caption[]` command in the main heading. If the optional argument to `\caption` is empty, no entry is made in the list of tables. Alternatively, if you do not want the table number to be printed each time, use the `\caption*` command.

The captions are set based on the code for the `article` class. If you have re-defined the standard `\@makecaption` command to produce a different format for the captions, you may need to make similar changes to the `longtable` version, `LT@makecaption`. See the code section for more details.

A more convenient method of customising captions is given by the `caption(2)` package, which provides commands for customising captions, and arranges that the captions in standard environments, and many environments provided by packages (including `longtable`) are modified in a compatible manner.

You may use the `\label` command so that you can cross reference `longtables` with `\ref`. Note, however, that the `\label` command should not be used in a heading that may appear more than once. Place it either in the `firsthead`, or in the body of the table. It should not be the `first` command in any entry.

5 Multicolumn entries

The `\multicolumn` command may be used in `longtable` in exactly the same way as for `tabular`. So you may want to skip this section, which is rather technical, however coping with `\multicolumn` is one of the main problems for an environment such as `longtable`. The main effect that a user will see is that certain combinations of `\multicolumn` entries will result in a document needing more runs of `LATEX` before the various ‘chunks’ of a table align.

The examples in this section are set with `LTchunksize` set to the minimum value of one, to demonstrate the effects when `\multicolumn` entries occur in different chunks.

Consider Table 3. In the second chunk, `longtable` sees the wide multicolumn entry. At this point it thinks that the first two columns are very narrow. All the width of the multicolumn entry is assumed to be in the third column. (This is a ‘feature’ of `TEX`’s primitive `\halign` command.) `longtable` then passes the

Table 3: A difficult `\multicolumn` combination: pass 1

1	2	3
wide multicolumn spanning 1-3		
multicolumn 1-2		3
wide 1	2	3

Table 4: A difficult `\multicolumn` combination: pass 2

1	2	3
wide multicolumn spanning 1-3		
multicolumn 1-2		3
wide 1	2	3

Table 5: A difficult `\multicolumn` combination: pass 3

1	2	3
wide multicolumn spanning 1-3		
multicolumn 1-2		3
wide 1	2	3

Table 6: A difficult `\multicolumn` combination: pass 4

1	2	3
wide multicolumn spanning 1-3		
multicolumn 1-2		3
wide 1	2	3

information that there is a wide third column to the later chunks, with the result that the first pass over the table is too wide.

If the 'saved row' from this first pass was re-inserted into the table on the next pass, the table would line up in two passes, but would be much too wide.

`\kill` The solution to this problem used in Versions 1 and 2, was to use a `\kill` line. If a line is `\killed`, by using `\kill` rather than `\` at the end of the line, it is used in calculating column widths, but removed from the final table. Thus entering `\killed` copies of the last two rows before the wide multicolumn entry would mean that `\halign` 'saw' the wide entries in the first two columns, and so would not widen the third column by so much to make room for the multicolumn entry.

In Version 3, a new solution was introduced. If the saved row in the `.aux` file was not being used, `longtable` used a special 'draft' form of `\multicolumn`, this modified the definition, so the spanning entry was never considered to be wider than the columns it spanned. So after the first pass, the `.aux` file stored the widest normal entry for each column, no column was widened due to `\spanned` columns. By default `longtable` ignored the `.aux` file, and so each run of `LATEX` was considered a first pass. Once the `\setlongtables` declaration was given, the saved row in the `.aux` file, and the proper definition of `\multicolumn` were used. If any `\multicolumn` entry caused one of the columns to be widened, this information could not be passed back to earlier chunks, and so the table would not correctly line up until the third pass. This algorithm always converged in three passes as described above, but in examples such as the ones in Tables 3-6, the final widths were not optimal as the width of column 2, which is determined by a `\multicolumn` entry, was not known when the final width for column 3 was fixed, due to the fact that *both* `\multicolumn` commands were switched from 'draft' mode to 'normal' mode at the same time.

Version 4 alleviates the problem considerably. The first pass of the table will indeed have the third column much too wide. However, on the next pass `longtable` will notice the error and reduce the column width accordingly. If this has to propagate to chunks before the `\multicolumn` one, an additional pass will, of course, be needed. It is possible to construct tables where this rippling up of the correct widths takes several passes to 'converge' and produce a table with all chunks aligned. However in order to need many passes one needs to construct a table with many overlapping `\multicolumn` entries, all being wider than the natural widths of the columns they span, and all occurring in different chunks. In the typical case the algorithm will converge after three or four passes, and the benefits of not needing to edit the document before the final run to add `\setlongtables`, and the better choice of final column widths in the case of multiple `\multicolumn` entries will hopefully more than pay for the extra passes that may possibly be needed.

So Table 3 converges after 4 passes, as seen in Table 6.

You can still speed the convergence by introducing judicious `\kill` lines, if you happen to have constellations like the above.

If you object even to `LATEX`-ing a file twice, you should make the first line of every `longtable` a `\kill` line that contains the widest entry to be used in each column. All chunks will then line up on the first pass.

6 Adjustment

The optional argument of `longtable` controls the horizontal alignment of the table. The possible options are `[c]`, `[r]` and `[l]`, for centring, right and left adjustment, respectively. Normally centring is the default, but this document specifies

```
\LTleft \setlength\LTleft\parindent
\LTRight \setlength\LTRight\fill
```

in the preamble, which means that the tables are set flush left, but indented by the usual paragraph indentation. Any lengths can be specified for these two parameters, but at least one of them should be a rubber length so that it fills up the width of the page, unless rubber lengths are added between the columns using the `\extracolsep` command. For instance

```
\begin{tabular*}{\textwidth}{@{\extracolsep{...}}...}
```

produces a full width table, to get a similar effect with `longtable` specify

```
\setlength\LTleft{0pt}
\setlength\LTRight{0pt}
\begin{longtable}{@{\extracolsep{...}}...}
```

7 Changes

This section highlights the major changes since version 2. A more detailed change log may be produced at the end of the code listing if the `ltxdoc.cfg` file specifies

```
\AtBeginDocument{\RecordChanges}
\AtEndDocument{\PrintChanges}
```

Changes made between versions 2 and 3.

- The mechanism for adding the head and foot of the table has been completely rewritten. With this new mechanism, `longtable` does not need to issue a `\clearpage` at the start of the table, and so the table may start half way down a page. Also the `\endlastfoot` command, which could not safely be implemented under the old scheme, has been added.
- `longtable` now issues an error if started in the scope of `\twocolumn`, or the `multicols` environment.
- The separate documentation file `longtable.tex` has been merged with the package file, `longtable.dtx` using Mittelbach's `doc` package.
- Support for footnotes has been added. Note however that `\footnote` will not work in the 'head' or 'foot' sections of the table. In order to put a footnote in those sections (e.g., inside a caption), use `\footnotemark` at that point, and `\footnotetext` anywhere in the table *body* that will fall on the same page.
- The treatment of `\multicolumn` has changed, making `\kill` lines unnecessary, at the price of sometimes requiring a third pass through L^AT_EX.
- The `\newpage` command now works inside a `longtable`.

Changes made between versions 3 and 4.

- A new algorithm is used for aligning chunks. As well as the widest width in each column, `longtable` remembers which chunk produced this maximum. This allows it to check that the maximum is still achieved in later runs. As `longtable` can now deal with columns shrinking as the file is edited, the `\setlongtables` system is no longer needed and is disabled.
- An extra benefit of the new algorithm's ability to deal with 'shrinking' columns is that it can give better (narrower) column widths in the case of overlapping `\multicolumn` entries in different chunks than the previous algorithm produced.
- The 'draft' multicolumn system has been removed, along with related commands such as `\LTmulticolumn`.
- The disadvantage of the new algorithm is that it can take more passes. The theoretical maximum is approximately twice the length of a 'chain' of columns with overlapping `\multicolumn` entries, although in practice it usually converges as fast as the old version. (Which always converged in three passes once `\setlongtables` was activated.)
- `\!* and \nepagebreak` commands may be used to control page breaking.

8 Summary

Table 7: A summary of `longtable` commands

Parameters		
<code>\LTleft</code>	Glue to the left of the table.	<code>(\fill)</code>
<code>\LTright</code>	Glue to the right of the table.	<code>(\fill)</code>
<code>\LTpre</code>	Glue before the table.	<code>(\bigskipamount)</code>
<code>\LTpost</code>	Glue after the table.	<code>(\bigskipamount)</code>
<code>\LTcapwidth</code>	The width of a parbox containing the caption.	<code>(4in)</code>
<code>LTchunksize</code>	The number of rows per chunk.	<code>(20)</code>
Optional arguments to <code>\begin{longtable}</code>		
<code>none</code>	Position as specified by <code>\LTleft</code> and <code>\LTright</code> .	
<code>[c]</code>	Centre the table.	
<code>[l]</code>	Place the table flush left.	
<code>[r]</code>	Place the table flush right.	
Commands to end table rows		
<code>\!</code>	Specifies the end of a row	
<code>\![(dim)]</code>	Ends row, then adds vertical space (as in the <code>tabular</code> environment).	
<code>\!*</code>	The same as <code>\!</code> but disallows a page break after the row.	
<code>\tabularnewline</code>	Alternative to <code>\!</code> for use in the scope of <code>\raggedright</code> and similar commands that redefine <code>\!</code> .	
<code>\kill</code>	Row is 'killed', but is used in calculating widths.	
<code>\endhead</code>	Specifies rows to appear at the top of every page.	
<code>\endfirsthead</code>	Specifies rows to appear at the top of the first page.	

`\endfoot` Specifies rows to appear at the bottom of every page.
`\endlastfoot` Specifies rows to appear at the bottom of the last page.

longtable caption commands

`\caption{<caption>}` Caption ‘Table ?: <caption>’, and a ‘<caption>’ entry in the list of tables.
`\caption[<lot>]{<caption>}` Caption ‘Table ?: <caption>’, and a ‘<lot>’ entry in the list of tables.
`\caption[]{<caption>}` Caption ‘Table ?: <caption>’, but no entry in the list of tables.
`\caption*{<caption>}` Caption ‘<caption>’, but no entry in the list of tables.

Commands available at the start of a row

`\pagebreak` Force a page break.
`\pagebreak[<val>]` A ‘hint’ between 0 and 4 of the desirability of a break.
`\nopagebreak` Prohibit a page break.
`\nopagebreak[<val>]` A ‘hint’ between 0 and 4 of the undesirability of a break.
`\newpage` Force a page break.

Footnote commands available inside longtable

`\footnote` Footnotes, but may not be used in the table head & foot.
`\footnotemark` Footnotemark, may be used in the table head & foot.
`\footnotetext` Footnote text, use in the table body.

Setlongtables

`\setlongtables` Obsolete command. Does nothing now.

9 Verbatim highlights from Table 1

```
\begin{longtable}{@{*}r||p{1in}@{*}}
KILLED & LINE!!!! \kill
\caption[An optional table caption ...]{A long table\label{long}}\
\hline\hline
\multicolumn{2}{@{*}c@{*}}%
    {This part appears at the top of the table}\
\textsc{First}&\textsc{Second}\
\hline\hline
\endfirsthead
\caption[]{{(continued)}\
\hline\hline
\multicolumn{2}{@{*}c@{*}}%
    {This part appears at the top of every other page}\
\textbf{First}&\textbf{Second}\
\hline\hline
\endhead
\hline
This goes at the&bottom.\
\hline
\endfoot
\hline
These lines will&appear\
in place of the & usual foot\
at the end& of the table\
\hline
\endlastfoot
\env{longtable} columns are specified& in the \
same way as in the \env{tabular}& environment.\
...
\multicolumn{2}{||c||}{This is a ...}\
...
Some lines may take...&
    \raggedleft This last column is a ‘p’ column...
    \tabularnewline
...
Lots of lines& like this.\
...
\hline
Lots\footnote{...} of lines& like this.\
Lots of lines& like this\footnote{...}\
\hline
Lots of lines& like this.\
...
\end{longtable}
```

10 The Macros

1 (*package)

10.1 Initial code

Before declaring the package options, we must define some defaults here.

`\LT@err` The error generating command
2 `\def\LT@err{\PackageError{longtable}}`

`\LT@warn` The warning generating command
3 `\def\LT@warn{\PackageWarning{longtable}}`

`\LT@final@warn` If any longtables have not aligned, generate a warning at the end of the run at `\AtEndDocument`.

4 `\def\LT@final@warn{%`
5 `\AtEndDocument{%`
6 `\LT@warn{Table \@width s have changed. Rerun LaTeX.\@gobbletwo}}%`
7 `\global\let\LT@final@warn\relax}`

10.2 Options

The first two options deal with error handling. They are compatible with the options used by the `tracefmt` package.

`errorshow` *Only* show errors on the terminal. ‘warnings’ are just sent to the log file.

8 `\DeclareOption{errorshow}{%`
9 `\def\LT@warn{\PackageInfo{longtable}}}`

`pausing` Make every warning message into an error so `TEX` stops. May be useful for debugging.

10 `\DeclareOption{pausing}{%`
11 `\def\LT@warn#1{%`
12 `\LT@err{#1}{This is not really an error}}}`

`set` The next options are just alternative syntax for the `\setlongtables` declaration.

`final` 13 `\DeclareOption{set}{}`
14 `\DeclareOption{final}{}`

15 `\ProcessOptions`

10.3 User Settable Parameters

`\LTleft` Glue to the left and right of the table, default `\fill` (ie centred).

`\LTright` 16 `\newskip\LTleft` `\LTleft=\fill`
17 `\newskip\LTright` `\LTright=\fill`

`\LTpre` Glue before and after the longtable. `\bigskip` by default.

`\LTpost` 18 `\newskip\LTpre` `\LTpre=\bigskipamount`
19 `\newskip\LTpost` `\LTpost=\bigskipamount`

`\LTchunksize` Chunk size (the number of rows taken per `\halign`). Default 200.

20 `\newcount\LTchunksize` `\LTchunksize=200`

.....longtable.sty.....

`\c@LTchunks` Added in V3.07 to allow the \LaTeX syntax `\setcounter{LTchunks}{10}`.
21 `\let\c@LTchunks\LTchunks`

`\LTcapwidth` Width of the `\parbox` containing the caption. Default 4in.
22 `\newdimen\LTcapwidth \LTcapwidth=4in`

`\LTcaptype` The name used as counter, in caption, `\addcontentsline` and in targets.
`\providecommand` is used for compability with `lcaption`
23 `\providecommand\LTcaptype{table}`

10.4 Internal Parameters

`\LT@head` Boxes for the table head and foot.

`\LT@firsthead` 24 `\newbox\LT@head`

`\LT@foot` 25 `\newbox\LT@firsthead`

`\LT@lastfoot` 26 `\newbox\LT@foot`
27 `\newbox\LT@lastfoot`

`\LT@gbox`
28 `\newbox\LT@gbox`

`\LT@cols` Counter for number of columns.
29 `\newcount\LT@cols`

`\LT@rows` Counter for rows up to chunksize.
30 `\newcount\LT@rows`

`\c@LT@tables` Counter for the tables, added in V3.02. Previous versions just used the \LaTeX counter `table`, but this fails if `table` is reset during a document, eg `report` class resets it every chapter.
This was changed from `\newcount\LT@tables` in V3.04. \LaTeX counters are preserved correctly when `\includeonly` is used. In the rest of the file `\LT@tables` has been replaced by `\c@LT@tables` without further comment.
31 `\newcounter{LT@tables}`
32 `\providecommand\theLT@tables{\theLT@tables}`

`\c@LT@chunks` We need to count through the chunks of our tables from Version 4 on.
33 `\newcounter{LT@chunks}[LT@tables]`

`\c@table` If the `table` counter is not defined (eg in `letter` style), define it. (Added in `\fnum@table` V3.06.)

`\tablename` 34 `\ifx\c@table\undefined`

`\ext@table` 35 `\newcounter{table}`
36 `\def\fnum@table{\tablename~\thetable}`
37 `\fi`
38 `\ifx\tablename\undefined`
39 `\def\tablename{Table}`
40 `\fi`
41 `\ifx\ext@table\undefined`
42 `\def\ext@table{lot}`
43 `\fi`

.....Page 13.....

.....longtable.sty.....

`\LT@out` In a normal style, `longtable` uses the `.aux` file to record the column widths. With `letter.sty`, use a separate `.lta` file. (Added in V3.06.)
Not needed for new letter class.

```
\ifx\startlabels\undefined
  \let\@auxout\@auxout
\else
  {\input{\jobname.lta}}%
  \newwrite\@auxout
  \immediate\openout\@auxout=\jobname.lta
\fi
```

`\LT@p@ftn` Temporary storage for footnote text in a ‘p’ column.
44 `\newtoks\LT@p@ftn`

`\LT@end@pen` Special penalty for the end of the table. Done this way to save using up a count register.
45 `\mathchardef\LT@end@pen=30000`

10.5 The `longtable` environment

`\longtable` Called by `\begin{longtable}`. This implementation does not work in multiple column formats. `\par` added at V3.04.

```
46 \def\longtable{%
47   \par
48   \if@noskipsec\mbox{}\par\fi
49   \@nbreakfalse
50   \ifx\multicols\@undefined
51     \else
52       \ifnum\col@number>\@ne
53         \@twocolumntrue
54       \fi
55     \fi
56     \if@twocolumn
57       \LT@err{longtable not in 1-column mode}\@ehc
58     \fi
59   \UseTaggingSocket{tbl/vmode/begin}%
60   \begingroup
```

Check for an optional argument.

```
61 \@ifnextchar[\LT@array{\LT@array[x]}]
```

`\LT@array`

```
62 (@@=tbl)
63 \ExplSyntaxOn
```

Start setting the alignment. Based on `\@array` from the \LaTeX kernel and the `array` package.

Since Version 3.02, `longtable` has used the internal counter `\c@LT@tables`. The \LaTeX counter `table` is still incremented so that `\caption` works correctly.

```
64 \def\LT@array[#1]#2{%
```

.....Page 14.....

With respect to tagging we have a complicated situation with longtable. When at the begin the `\endhead`, `\endfirsthead`, `\endfoot` and `\endlastfoot` are used to setup head and foot they create each a structure subtree with one or more rows. From these structures we want to keep at most two (head and foot) and move the foot to the end of the table. When the head and foot boxes are (re)inserted on following pages we want to mark them up as artifact with the exception of the head at the begin and the foot box at the end.

TODO: When a line is killed the structure subtree is there already too and must be removed. If hard to do, then maybe at first warn if the construction is used.

`\LT@array` is executed in a group, so we can disable para-tagging here.

```

65 \UseTaggingSocket{tbl/init}
66 \tl_if_empty:eTF { \LTcapytype }
67   {
68     \tl_gset:Ne \@currentHref {LT@tables.\theHLT@tables}
69   }
70   {
71     \@kernel@refstepcounter{\LTcapytype}\stepcounter{LT@tables}

```

The target is created rather late and a `\label` can come earlier, so we have to define `\@currentHref` explicitly. We can't currently assume that `\theHtable` is defined always.

```

72     \tl_gset:Ne \@currentHref {\LTcapytype.\cs_if_exist_use:c {theH\LTcapytype}}
73   }
74 \tbl_gzero_row_count:
75 \UseTaggingSocket{tbl/longtable/init}

```

Set up the glue around the table if an optional argument given.

```

76 \if l#1%
77   \LTleft\z@ \LTright\fill
78 \else\if r#1%
79   \LTleft\fill \LTright\z@
80 \else\if c#1%
81   \LTleft\fill \LTright\fill
82 \fi\fi\fi

```

Set up these internal commands for longtable.

```

\global\let\LT@mcw@rn\relax
83 \let\LT@mc@l\multicolumn

```

Now redefine `\@tabarray` to restore `\hline` and `\multicolumn` so that arrays and tabulars nested in longtable (or in page headings on longtable pages) work out OK. Saving the original definitions done here so that you can load the `array` package before or after longtable.

```

84 \let\LT@@@@tabarray\@tabarray
85 \let\LT@@@@hl\hline
86 \def\@tabarray{%
87   \let\hline\LT@@@@hl

\let\multicolumn\LT@mc@l

```

.....longtable.sty.....

```
88 \LT@@@tabarray}%
89 \let\\LT@tabularcr
90 \let\tabularnewline\\%
91 \def\newpage{\noalign{\break}}%
```

More or less standard definitions, but first start a `\noalign`.

```
92 \def\pagebreak{\noalign{\ifnum' }=0\fi\@testopt{\LT@no@pgbk-}4}%
93 \def\nopagebreak{\noalign{\ifnum' }=0\fi\@testopt\LT@no@pgbk4}%
94 \let\hline\LT@hline \let\kill\LT@kill\let\caption\LT@caption
95 \@tempdima\ht\strutbox
96 \let\@endpbox\LT@endpbox
```

Set up internal commands according to Lamport or Mittelbach.

```
97 \ifx\extrarowheight\@undefined
```

Initialise these commands as in `tabular` from the L^AT_EX kernel.

```
98 \let\@acol\@tabacol
99 \let\@classz\@tabclassz \let\@classiv\@tabclassiv
100 \def\@startpbox{\vtop\LT@startpbox}%
101 \let\@@@startpbox\@startpbox
102 \let\@@@endpbox\@endpbox
103 \let\LT@LL@FM@cr\@tabularcr
104 \else
```

Initialise these commands as in `array`. `\d@llar` replaced by `\d@llarbegin` `\d@llarend` in V3.03 to match `array` V2.0h. We do not need to set `\d@llarbegin` and `\d@llarend` as the `array` package gives them the correct values at the top level.

```
105 \advance\@tempdima\extrarowheight
106 \col@sep\tabcolsep
107 \let\@startpbox@action\LT@startpbox
108 \let\LT@LL@FM@cr\@arraycr
109 \fi
```

The rest of this macro is mainly based on `array` package, but should work for the standard `tabular` too.

```
110 \setbox\@arstrutbox\hbox{\vrule
111 \@height \arraystretch \@tempdima
112 \@depth \arraystretch \dp \strutbox
113 \@width \z@}%
114 \let\@sharp#\let\protect\relax
```

Interpret the preamble argument.

```
115 \begingroup
116 \mkpream{#2}%
117 \tbl_count_table_cols:
```

We need to rename `\@preamble` here as F.M.'s scheme uses `\global`, and we may need to nest `\mkpream`, eg for `\multicolumn` or an `array`. We do not need to worry about nested longtables though!

```
118 \xdef\LT@bchunk{%
```

We aren't inside any row when a chunk starts.

```
119 \tbl_inbetween_rows:
```

.....Page 16.....

.....longtable.sty.....

```
120     \global\advance\c@LT@chunks\@ne
121     \global\LT@rows\z@\setbox\z@\vbox\bgroup
```

The following line was added in v4.05. In order to get the `\penalties` to work at chunk boundaries, we need to take more care about where and when `\lineskip` glue is added. The following does nothing at top of table, and in header chunks, but in normal body chunks it sets `\prevdepth` (to 0pt, but any value would do) so that `\lineskip` glue will be added. The important thing to note is that the glue will be added *after* any vertical material coming from `\noalign`.

```
122     \LT@setprevdepth
123     \tabskip\LTleft \noexpand\halign to\hsize\bgroup
124 %     \tabskip\LTleft\halign to\hsize\bgroup
125     \tabskip\z@ \@arstrut
```

Insert the tagging socket to start the row and initialize the cell data for the row.

```
126     \UseTaggingSocket{tbl/row/begin}%
127     \tbl_init_cell_data_for_row:
128     \@preamble \tabskip\LTright \cr}%
129 \endgroup
```

Find out how many columns we have (store in `\LT@cols`).

```
130 \expandafter\LT@nofcols\LT@bchunk&\LT@nofcols
```

Get the saved row from `\LT@i... \LT@ix` (from the `.aux` file), or make a new blank row.

```
131 \LT@make@row
```

A few more internal commands for `longtable`.

```
132 \m@th\let\par\@empty
```

Tagging socket and conditional

```
133 \everycr{%
134     \noalign{%
```

In `longtable` we have a bunch of extra `\crs` that are executed whenever a chunk ends. In that case they should not increment the main row counter, sigh.

TODO: At the moment this tracing still exposes the internal row counter!

```
135     \@@_trace:n {--longtable-->~chunk~row:~ \the\LT@rows \space
136                 row:~ \the\g_@@_row_int \space
137                 column:~ \the\g_@@_col_int
138     }
```

```
139     \tbl_if_row_was_started:T
140     {
141         \UseTaggingSocket{tbl/row/end}
```

The next setting prevents any of the additional `\crs` at the end of the chunk to add another `/TR`. Then once we really start a new chunk it gets incremented so...

```
142     \tbl_inbetween_rows:
143     }
```

And for the same reason such `\crs` should not increment the main row counter (but it has to be incremented after the preamble of a chunk), so here we test against `\LT@rows` which is `\LTchunksize` at the end of a chunk.

```
144     \int_compare:nNnT \LT@rows < \LTchunksize
```

.....Page 17.....

.....longtable.sty.....

```
145      { \tbl_gincr_row_count: } % next is row about to start
146    }%
147  }%
148  \lineskip\z@\baselineskip\z@
Start the first chunk.
149  \LT@bchunk}
150  \ExplSyntaxOff
151  (@@=)
```

`\LT@no@pgbk` Can simplify the standard `\no@pgbk` as this is vmode only but then need to close the `\noalign`.

```
152 \def\LT@no@pgbk#1[#2]{\penalty #1\getpen{#2}\ifnum'{-0\fi}}
```

`\LT@start` This macro starts the process of putting the table on the current page. It is not called until either a `\` or `\endlongtable` command ends a chunk, as we do not know until that point which of the four possible head or foot sections have been specified.

It begins by redefining itself, so that the table is only started once! Until V3.04, was redefined to `\relax`, now use `\endgraf` to force the page-breaker to wake up. The second `\endgraf` is there so that `\pagetotal` is updated and so takes `\LTpre` into account.

```
153 (@@=tbl)
154 \ExplSyntaxOn
155 \def\LT@start{%
156   \let\LT@start\endgraf
157   \endgraf\penalty\z@\vskip\LTpre\endgraf
```

This next block was suggested by Lars Hellström in pr tools/3396. He documents it as:

The original problem occurs because TeX has not yet found an awfully bad (`b=*`) breakpoint and is therefore still collecting material to see if there is a really good break somewhere just ahead. As we know there aren't, we want to make it stop looking and break the page, so that `\pagetotal` will be for the page where the table will actually end up. To achieve this, we need to give TeX an awfully bad, but legal, breakpoint. The simplest way of doing this seems to be to insert a `\kern` that counters the `\pageshrink` for the page, followed by a `\penalty` and a `\par` (to exercise the page builder). We also have to make sure that this breakpoint doesn't affect how the next page is broken, so we make the penalty 9999 (10000 is infinite and thus not a legal breakpoint) and cancel out the `\kern` with a new `\kern`.

I don't think this is the *right* solution to the problem (that would be that the standard output routine has a feature for synchronizing with typesetting, as part of the preparations for switching output routine), but it's OK. Perhaps XOR will make it better.

```
158   \ifdim \pagetotal<\pagegoal \else
159     \dimen@=\pageshrink
160     \advance \dimen@ 1sp %
161     \kern\dimen@\penalty 9999\endgraf \kern-\dimen@
162   \fi
```

.....Page 18.....

.....longtable.sty.....

Start a new page if there is not enough room for the table head, foot, and one extra line.

```
163 \dimen@\pagetotal
164 \advance\dimen@ \ht\ifvoid\LT@firsthead\LT@head\else\LT@firsthead\fi
165 \advance\dimen@ \dp\ifvoid\LT@firsthead\LT@head\else\LT@firsthead\fi
166 \advance\dimen@ \ht\LT@foot
```

At this point I used to add `\ht\@arstrutbox` and `\dp\@arstrutbox` as a measure of a row size. However this can fail spectacularly for `p` columns which might be much larger. Previous versions could end up with the table starting with a foot, then a page break then a head *then* a 'first head'! So now measure the first line of the table accurately by `\vsplitting` it out of the first chunk.

```
167 \edef\LT@reset@vfuzz{\vfuzz\the\vfuzz\vbadness\the\vbadness\relax}%
168 \vfuzz\maxdimen
169 \vbadness\@M
170 \setbox\tw@\copy\z@
171 \setbox\tw@\vsplit\tw@ to \ht\@arstrutbox
172 \setbox\tw@\vbox{\unvbox\tw@}%
173 \LT@reset@vfuzz
174 \advance\dimen@ \ht
175 \ifdim\ht\@arstrutbox>\ht\tw@\@arstrutbox\else\tw@\fi
176 \advance\dimen@\dp
177 \ifdim\dp\@arstrutbox>\dp\tw@\@arstrutbox\else\tw@\fi
178 \advance\dimen@ -\pagegoal
179 \ifdim \dimen@>\z@
180 \vfil\break
181 \else
```

The LT output routine does not handle shrink on the page, which can cause the first page to be over-long, so forget it is there.

```
182 \ifdim\pageshrink>\z@\pageshrink\z@\fi
183 \fi
```

Store height of page minus table foot in `\@colroom`.

```
184 \global\@colroom\colht
```

If the foot is non empty, reduce the `\vsize` and `\@colroom` accordingly.

```
185 \ifvoid\LT@foot\else
186 \global\advance\vsize-\ht\LT@foot
187 \global\advance\@colroom-\ht\LT@foot
188 \dimen@\pagegoal\advance\dimen@-\ht\LT@foot\pagegoal\dimen@
189 \maxdepth\z@
190 \fi
191 \tl_if_empty:eTF{\LTcapytype}
192 {
193 \MakeLinkTarget{LT@tables}
194 }
195 {
196 \MakeLinkTarget{\LTcapytype}
197 }
```

Put the table head on the page, and then switch to the new output routine.

```
198 \ifvoid\LT@firsthead\copy\LT@head\else\box\LT@firsthead\fi\nobreak
199 \UseTaggingSocket{tbl/longtable/head}
```

.....Page 19.....

.....longtable.sty.....

```
200 \output{\LT@output}}
201 \ExplSyntaxOff
202 (@@=)
```

\endlongtable

```
203 (@@=tbl)
204 \ExplSyntaxOn
```

Called by \end{longtable}.

```
205 \def\endlongtable{%
```

Essentially add a final \\. But as we now know the number of actual chunks, we first strip away all entries referring to a maximum entry beyond the table (this can only happen if a table has been shortened, or the table numbering has gone awry). In that case we at least start collecting valid new information with the last chunk of this table, by removing the width constraint.

```
206 \tbl_crcr:n {endlongtable}
207 \noalign{%
208 \UseTaggingSocket{tbl/longtable/finalize}
209 \let\LT@entry\LT@entry@chop
210 \xdef\LT@save@row{\LT@save@row}}%
211 \LT@echunk
212 \LT@start
213 \unvbox\z@
214 \LT@get@widths
```

Write the dummy row to the .aux file. Since V3.06, use .lta for letter.sty.

```
215 \if@filesw
216 {\let\LT@entry\LT@entry@write\immediate\write\@auxout{%
```

Since Version 3.02, longtable has used the internal counter \c@LT@tables rather than the L^AT_EX counter table. This information looks entirely different from version 3 information. Still, we don't need to rename the macro name because later code will consider the information to have no columns, and thus will throw the old data away.

```
217 \gdef\expandafter\noexpand
218 \csname LT@romannumeral\c@LT@tables\endcsname
219 {\LT@save@row}}%
220 \fi
```

At this point used to issue a warning if a \multicolumn has been set in draft mode.

```
\LT@mcw@rn
```

If the last chunk has different widths than the first, warn the user. Also trigger a warning to rerun L^AT_EX at the end of the document.

```
221 \ifx\LT@save@row\LT@@@save@row
222 \else
223 \LT@warn{Column~ widths~ have~ changed\MessageBreak
224 in~
225 \t1_if_empty:eTF{\LTcaptive}
226 {longtable~ \theLT@tables}
227 {\LTcaptive\c_space_t1\use:c{the\LTcaptive}}}
```

.....Page 20.....

.....longtable.sty.....

```
228     }
229     \LT@final@warn
230 \fi
```

Force one more go with the longtable output routine. Guard the special start of page value of \pagegoal.

```
231 \endgraf\penalty -\LT@end@pen
232 \ifvoid\LT@foot\else
233   \global\advance\vsizelt\LT@foot
234   \global\advance\colroom\ht\LT@foot
235   \ifdim\pagegoal<\maxdimen
236     \dimen@pagegoal\advance\dimen@\ht\LT@foot\pagegoal\dimen@
237   \fi
238 \fi
```

Now close the group to return to the standard routine.

```
239 \endgroup
```

Reset \@mparbottom to allow marginpars close to the end of the table.⁵

```
240 \global\@mparbottom\z@
241 % \pagegoal\vsizelt
242 \endgraf\penalty\z@addvspace\LTpost
```

Footnotes. As done in the multicol package.

```
243 \ifvoid\footins\else\insert\footins{}\fi
244 \UseTaggingSocket{tbl/vmode/end}%
245 }
246 \ExplSyntaxOff
247 (@@=)
```

10.6 Counting Columns

Columns are counted by examining \@preamble, rather than simply getting \@mkpream to increment the counter as it builds the preamble so that this package works with many of the packages which add extra column specifiers to L^AT_EX's standard ones.

Version 1 counted \@sharp's to calculate the number of columns, this was changed for Version 2 as it does not work with the NFSS. Now count &'s. (lfonts.new (and now the Standard L^AT_EX definition) defines \@tabclassz so that \@sharp is inside a group.)

\LT@nofcols Find the next &, then look ahead to see what is next.

```
248 \def\LT@nofcols#1&{%
249   \futurelet\@let@token\LT@nofcols}
```

\LT@nofcols Add one, then stop at an \LT@nofcols or look for the next &. The \expandafter trick was added in Version 3, also the name changed from \@LT@nofcols to preserve the \LT@ naming convention.

```
250 \def\LT@nofcols{%
251   \advance\LT@cols\@ne
252   \ifx\@let@token\LT@nofcols
```

⁵This can not be the correct. However if it is omitted, there is a problem with marginpars, for example on page 3 of this document. Any Output Routine Gurus out there?

.....longtable.sty.....

```
253 \expandafter\@gobble
254 \else
255 \expandafter\LT@nofcols
256 \fi}
```

10.7 The `\` and `\kill` Commands

`\LT@tabularcr` The internal definition of `\`. In the `*` form, insert a `\nobreak` after the next `\cr` (or `\crr`).

This star form processing was finally added in v4.05. For the previous six or seven years the comment at this point said

This definition also accepts `*`, which acts in the same way as `\. tabular` does this, but `longtable` probably ought to make `*` prevent page breaking.

`{\ifnum0='}\fi` added in version 3.01, required if the first entry is empty. The above in fact is not good enough, as with `array` package it can introduce a `{}` group in math mode, which changes the spacing. So use the following variant. Added in v3.14.

```
257 \protected\def\LT@tabularcr{%
258 \relax\iffalse{\fi\ifnum0='}\fi
259 \@ifstar
```

TODO: as we replace `crr` later in one case, we probably have to implement some further logic there!

```
260 {\def\crr{\LT@crr\noalign{\nobreak}}\let\cr\crr
261 \LT@t@bularcr}%
262 {\LT@t@bularcr}}
```

`\LT@crr`

```
263 \let\LT@crr\crr
```

`\LT@setprevdepth` This will be redefined to set the `\prevdepth` at the start of a chunk.

```
264 \let\LT@setprevdepth\relax
```

`\LT@t@bularcr`

```
265 (@@=tbl)
266 \ExplSyntaxOn
267 \def\LT@t@bularcr{%
```

Increment the counter, and do `tabular`'s `\` or finish the chunk.

The `\expandafter` trick was added in Version 3. Set the `\prevdepth` at the start of a new chunk. (Done here so not set in header chunks.)

```
268 \global\advance\LT@rows\@ne
269 \ifnum\LT@rows=\LTchunksize
```

At the end of the chunk `\` is doing something special and so we lose `\tbl_count_missing_cells:n`. Below is about the right place to add it do this code branch.

```
270 \tbl_count_missing_cells:n {echunk}
271 \gdef\LT@setprevdepth{%
272 \prevdepth\z@
273 \global\let\LT@setprevdepth\relax}%
274 \expandafter\LT@xtabularcr
275 \else
```

.....Page 22.....

.....longtable.sty.....

```
276 \ifnum0={}\fi
277 \expandafter\LT@LL@FM@cr
278 \fi}
279 \ExplSyntaxOff
280 (@@=)
```

`\LT@xtabularcr` This just looks for an optional argument.

```
281 \def\LT@xtabularcr{%
282 \@ifnextchar[\LT@argtabularcr\LT@ntabularcr}
```

`\LT@ntabularcr` The version with no optional argument. `\ifnum0={}\fi` added in version 3.01. Changed in 3.14.

```
283 \def\LT@ntabularcr{%
284 \ifnum0={}\fi
285 \LT@echunk
286 \LT@start
287 \unvbox\z@
288 \LT@get@widths
289 \LT@bchunk}
```

`\LT@argtabularcr` The version with an optional argument. `\ifnum0={}\fi` added in version 3.01. Changed in 3.14.

```
290 \def\LT@argtabularcr[#1]{%
291 \ifnum0={}\fi
292 \ifdim #1>\z@
293 \unskip\@xargarraycr{#1}%
294 \else
295 \@yargarraycr{#1}%
296 \fi
```

Add the dummy row, and finish the `\halign`.

```
297 \LT@echunk
298 \LT@start
299 \unvbox\z@
300 \LT@get@widths
301 \LT@bchunk}
```

`\LT@echunk` This ends the current chunk, and removes the dummy row.

```
302 \def\LT@echunk{%
303 \crr\LT@save@row\cr\egroup
304 \global\setbox\LT@gbox\lastbox
```

The following line was added in v4.05. `longtable` relies on `\lineskip` glue (which is 0pt) to provide break points between each row so the table may be split into pages.

Previous releases left the `\lineskip` glue at the end of each chunk that had been added when the dummy row was added. There was no glue at the start of the next chunk as \TeX normally does not put `\lineskip` glue at the top of a box. This meant that normally the chunks fitted together perfectly, however `\noalign` material at a chunk boundary came before the first row of the next chunk but after the `\lineskip` glue at the end of this chunk. This is the wrong place, e.g., it means even a `\penalty10000` does not stop a break as the `\lineskip` glue in the previous item on the list provides a legal breakpoint. So now remove the

.....longtable.sty.....

`\lineskip` glue that was before the dummy row and introduce `\LT@setprevdepth` to set the `\prevdepth` at the start of the next chunk, to make sure `\lineskip` glue is added later.

```
305 \unskip
306 \egroup}
```

`\LT@entry` We here give the ‘basic’ definition of `\LT@entry`, namely that used in alignment templates. It has a `\kern` only if the maximum is imposed from a different chunk. The `\ifhmode` test reveals the first entry, when we don’t want to add an `&`.

```
307 \def\LT@entry#1#2{%
308 \ifhmode\@firstofone{&}\fi\omit
309 \ifnum#1=\c@LT@chunks
310 \else
311 \kern#2\relax
312 \fi}
```

`\LT@entry@chop` This definition for the argument of `\LT@save@row` is used to scrap all those maxima which could not be verified because they occur after the end of the table. This can happen only if a table has been shortened (or the sequencing got mixed up) since the previous run. Note that this is premature: the last chunk still is going to be set, and with the chopped limits.

```
313 \def\LT@entry@chop#1#2{%
314 \noexpand\LT@entry
315 {\ifnum#1>\c@LT@chunks
316 1}{Opt%
317 \else
318 #1}{#2%
319 \fi}}
```

`\LT@entry@write` To write an entry for the aux file, we use a slightly surprising definition which has the sole purpose of avoiding overfull lines (which might break `TEX`’s limits when reading the aux file, probably you’d need to have a few hundred columns before this happened but...).

```
320 \def\LT@entry@write{%
321 \noexpand\LT@entry^^J%
322 \@spaces}
```

`\LT@kill` This ends the current chunk as above, but strips off two rows, the ‘dummy row’ and the ‘killed row’ before starting the next chunk. Since V3.04, the old chunk is reboxed at the start of the box containing the next chunk. This allows `\kill` to be used in headers, which must be processed in a single box.

```
323 \def\LT@kill{%
324 \LT@echunk
325 \LT@get@widths
326 \expandafter\LT@rebox\LT@bchunk}
```

`\LT@rebox` Drop the old chunk (box0) back at the top of the new chunk, removing the killed row. This macro added at V3.04.

```
327 \def\LT@rebox#1\bggroup{%
328 #1\bggroup
329 \unvbox\z@
330 \unskip
331 \setbox\z@\lastbox}
```

.....Page 24.....

10.8 The Dummy Row

The dummy row is kept inside of the macro `\LT@save@row`.

`\LT@blank@row` Create a blank row if we are not using the info in the `.aux` file.

```
\LT@build@blank 332 \def\LT@blank@row{%
333   \xdef\LT@save@row{\expandafter\LT@build@blank
334     \romannumeral\number\LT@cols 001 }}}
```

Whoops! What's that supposed to be? A drop-in replacement for the first task of Appendix D in the `TEXbook`. The `\romannumeral` produces `\LT@cols` instances of `m` followed by `i`. The below macro then replaces the `ms` by appropriate entries.

```
335 \def\LT@build@blank#1{%
336   \if#1m%
337     \noexpand\LT@entry{1}{0pt}%
338     \expandafter\LT@build@blank
339   \fi}
```

`\LT@make@row` Prior to version 4, by default did not use information in the `.aux` file but now we can define `\LT@make@row` to use the `.aux` file, even on the 'draft' passes.

```
340 \def\LT@make@row{%
341   \global\expandafter\let\expandafter\LT@save@row
342   \csname LT@\romannumeral\c@LT@tables\endcsname
343   \ifx\LT@save@row\relax
344     \LT@blank@row
```

Now a slightly difficult part comes. Before we decide making the template from the `.aux` file info we check that the number of fields has remained the same. If it hasn't, either the table format has changed, or we have the wrong table altogether. In both cases, we decide to better drop all gathered information and start over.

The expansion between `!...!` below will be empty if the number of `\LT@entry` macros including arguments in `\LT@save@row` is equal to `\LT@cols`. If it is not empty, we throw the row away and start from scratch.

```
345   \else
346     {\let\LT@entry\or
347     \if!%
348       \ifcase\expandafter\expandafter\expandafter\LT@cols
349       \expandafter@gobble\LT@save@row
350       \or
351       \else
352         \relax
353       \fi
354     !%
355     \else
356       \aftergroup\LT@blank@row
357     \fi}%
358   \fi}
```

`\setlongtables` Redefine `\LT@make@row` to use information in the `.aux` file, if there is a saved row for this table with the right number of columns.

Since Version 3.02, `longtable` has used the internal counter `\c@LT@tables` rather than the `LATEX` counter `table`. The warning message was added at V3.04, as was the `\global`, to stop save-stack overflow.

Since Version 4.01 `\setlongtables` does nothing as it is not needed, but is defined as `\relax` for the benefit of old documents.

```
359 \let\setlongtables\relax
```

`\LT@get@widths` This is the heart of `longtable`. If it were not for the table head and foot, this macro together with the modified `\` command would form the basis of quite a simple little package file for long tables. It is closely modelled on the `\endvrulealign` macro of appendix D of the `TEXbook`.

```
360 \def\LT@get@widths{%
```

`\global` added at V3.04, to stop save-stack overflow.

Loop through the last row, discarding glue, and saving box widths. At V3.04 changed the scratch box to 2, as the new `\kill` requires that `\box0` be preserved.

```
361 \setbox\tw@\hbox{%
362   \unhbox\LT@gbox
363   \let\LT@old@row\LT@save@row
364   \global\let\LT@save@row\@empty
365   \count@\LT@cols
366   \loop
367     \unskip
368     \setbox\tw@\lastbox
369     \ifhbox\tw@
370       \LT@def@row
371       \advance\count@\m@ne
372   \repeat}%
```

Remember the widths if we are in the first chunk.

```
373 \ifx\LT@@save@row\undefined
374   \let\LT@@save@row\LT@save@row
375 \fi}
```

`\LT@def@row` Add a column to the dummy row. Name changed from `\defLT@save@row` in Version 3, to preserve the `\LT@` naming convention.

```
376 \def\LT@def@row{%
```

We start by picking the respective entry from our old row. These redefinitions of `\LT@entry` are local to the group started in `\LT@get@widths`.

```
377 \let\LT@entry\or
378 \edef\@tempa{%
379   \ifcase\expandafter\count@\LT@old@row
380   \else
381     {1}{0pt}%
382   \fi}%
```

Now we tack the right combination in front of `\LT@save@row`:

```
383 \let\LT@entry\relax
384 \xdef\LT@save@row{%
385   \LT@entry
386   \expandafter\LT@max@sel\@tempa
387   \LT@save@row}}
```

`\LT@max@sel` And this is how to select the right combination. Note that we take the old maximum information only if the size does not change in *either* direction. If the size

.....longtable.sty.....

has grown, we of course have a new maximum. If the size has shrunk, the old maximum (which was explicitly not enforced because of being in the current chunk) is invalid, and we start with this chunk as the new size. Note that even in the case of equality we *must* use the `\the\wd\tw@` construct instead of `#2` because `#2` might be read in from the file, and so could have `\catcode 11` versions of `p` and `t` in it which we want to be replaced by their ‘proper’ `\catcode 12` versions.

```
388 \def\LT@max@sel#1#2{%
389   {\ifdim#2=\wd\tw@
390     #1%
391   \else
392     \number\c@LT@chunks
393   \fi}%
394 {\the\wd\tw@}}
```

10.9 The `\hline` Command

`\LT@hline` `\hline` and `\hline\hline` both produce *two* lines. The only difference being the glue and penalties between them. This is so that a page break at a `\hline` produces a line on both pages.⁶ Also this `\hline` is more like a `\cline{1-\LT@cols}`. `tabular`’s `\hline` would draw lines the full width of the page.

```
395 \def\LT@hline{%
396   \noalign{\ifnum0='}\fi
397   \penalty\@M
398   \futurelet\@let@token\LT@@hline}
```

`\LT@@hline` This code is based on `\cline`. Two copies of the line are produced, as described above.

```
399 (@@=tbl)
400 \ExplSyntaxOn
401 \def\LT@@@hline{%
402   \ifx\@let@token\hline
403     \global\let\@gtempa\@gobble
404     \gdef\LT@sep{\penalty-\@medpenalty\vskip\doublerulesep}%
405   \else
406     \global\let\@gtempa\@empty
407     \gdef\LT@sep{\penalty-\@lowpenalty\vskip-\arrayrulewidth}%
408   \fi
409   \ifnum0='{}\fi}%
410   \multispan\LT@cols
411   \unskip\leaders\hrule\@height\arrayrulewidth\hfill\cr
```

Don’t update the row counter, or rather undo the update done in `\everycr`:

```
412 \noalign{
413   \tbl_gdecr_row_count:
414   \LT@sep}
415 \multispan\LT@cols
416 \unskip\leaders\hrule\@height\arrayrulewidth\hfill\cr
```

Same here.

```
417 \noalign{
418   \tbl_gdecr_row_count:
```

⁶`longtable` has always done this, but perhaps it would be better if hlines were *omitted* at a page break, as the head and foot usually put a hline here anyway.

..... longtable.sty

```
419 \penalty\M}
420 \@gtempa}
421 (@@=)
```

10.10 Captions

`\LT@caption` The caption is `\multicolumn{\LT@cols}{c}{\langle a parbox with the table's caption \rangle}`

```
422 \def\LT@caption{%
423 \noalign\bgroup
424 \ifnextchar[{\egroup\LT@caption\@firstofone}\LT@caption}
```

`\LT@caption` Caption command (with [optional argument]). `\protect` added in Version 3. `\fnum@table` added at V3.05.

```
425 \def\LT@caption#1[#2]#3{
426 \tl_if_empty:eTF{\LTcaptiontype}
427 {\LT@makecaption\@gobble}{#3}}
428 {\LT@makecaption#1{\csname fnum@\LTcaptiontype\endcsname}{#3}
429 \def\@tempa{#2}
430 \ifx\@tempa\@empty\else
431 {\let\\space
432 \addcontentsline
433 {\@nameuse{ext@\LTcaptiontype}}
434 {\LTcaptiontype}
435 {\protect\numberline{\@nameuse{the\LTcaptiontype}}{#2}}}
436 \fi}}
437 \ExplSyntaxOff
```

`\LT@caption` Caption command (no [optional argument])

```
438 \def\LT@caption{%
439 \@ifstar
440 {\egroup\LT@caption\@gobble[]}%
441 {\egroup\@xdblarg{\LT@caption\@firstofone}}}
```

`\LT@makecaption` Put the caption in a box of width 0pt, so that it never affects the column widths. Inside that is a `\parbox` of width `\LTcapwidth`.

```
442 \def\LT@makecaption#1#2#3{%
443 \LT@mc\LT@cols c{\hbox to\z@{\hss\parbox[t]\LTcapwidth{%
```

Based on article class `\@makecaption`, #1 is `\@gobble` in star form, and `\@firstofone` otherwise.

```
444 \reset@font
445 \sbox\@tempboxa{#1{#2: }#3}%
446 \ifdim\wd\@tempboxa>\hsize
447 #1{#2: }#3%
448 \else
449 \hbox to\hsize{\hfil\box\@tempboxa\hfil}%
450 \fi
451 \endgraf\vskip\baselineskip}%
452 \hss}}}
```

10.11 The Output Routine

The method used here for interfacing a special purpose output routine to the standard \LaTeX routine is lifted straight out of F. Mittelbach's `multicol` package.

..... Page 28

.....longtable.sty.....

\LT@output Actually this is not so bad, with FM leading the way.

```
453 \ExplSyntaxOn
454 \def\LT@output{%
455   \ifnum\outputpenalty <-\@Mi
456   \ifnum\outputpenalty > -\LT@end@pen
If this was a float or a marginpar we complain.
457   \LT@err{floats~ and~ marginpars~ not~ allowed~ in~ a~ longtable}\@ehc
458   \else
```

We have reached the end of the table, on the scroll at least,

```
459   \setbox\z@\vbox{\unvbox\@cclv}%
460   \ifdim \ht\LT@lastfoot>\ht\LT@foot
```

The last foot might not fit, so:⁷

```
461   \dimen@\pagegoal
462   \advance\dimen@\ht\LT@foot
463   \advance\dimen@-\ht\LT@lastfoot
464   \ifdim\dimen@<\ht\z@
465     \setbox\@cclv\vbox{\unvbox\z@\copy\LT@foot\vss}%
466     \@makecol
467     \@expl@@@mark@update@singlecol@structures@@
468     \@outputpage
469     \global\vsizel\@colroom
470     \setbox\z@\vbox{\box\LT@head}%
```

End of \ifdim\dimen@<\ht\@cclc.

```
471   \fi
```

End of \ifdim \ht\LT@lastfoot > \ht\LT@foot.

```
472   \fi
```

Reset \@colroom.

```
473 %   \global\@colroom\@colht
474 %   \global\vsizel\@colht
```

Put the last page of the table on to the main vertical list.

```
475   \unvbox\z@\box\ifvoid\LT@lastfoot\LT@foot\else\LT@lastfoot\fi
```

Handle foot box when tagging:

```
476   \UseTaggingSocket{tbl/longtable/foot}
End of \ifnum\outputpenalty > -\LT@end@pen.
```

```
477   \fi
```

Else \outputpenalty > -\@Mi.

```
478   \else
```

If we have not reached the end of the table,

```
479   \setbox\@cclv\vbox{\unvbox\@cclv\copy\LT@foot\vss}%
```

Handle foot box when tagging:

```
480   \UseTaggingSocket{tbl/longtable/foot}
481   \@makecol
482   \@expl@@@mark@update@singlecol@structures@@
483   \@outputpage
```

⁷An alternative would be to vsplit off a bit of the last chunk, so that the last page did not just have head and foot sections, but it is hard to do this in a consistent manner.

.....longtable.sty.....

```

Reset \vsize.
484     \global\vsize\@colroom
Put the head at the top of the next page.
485     \copy\LT@head\nobreak
End of \ifnum\outputpenalty <-\@Mi.
486     \fi}
487 \ExplSyntaxOff
488 (@@=)

```

10.12 Commands for the table head and foot

```

\LT@end@hd@ft The core of \endhead and friends. Store the current chunk in the box specified
by #1. Issue an error if the table has already started. Then start a new chunk.
489 (@@=tbl)
490 \ExplSyntaxOn
491 \def\LT@end@hd@ft#1{%

```

This command is used to store the head and foot boxes. We need to retrieve and store the row so that we can clean up the structure in the finalize code. To handle missing columns in the header we need this:

```

492     \tbl_if_row_was_started:TF
493     {
TODO: This is exposing internal counters, so it should be encapsulated in some
interface command (but I'm not sure what that should be called, so not done yet.
494         \tbl_count_missing_cells:n {head/foot}
495         \int_step_inline:nn
496         { \LT@rows + 1 }
497         {
498             \seq_gput_left:ce
499             {g_@@\cs_to_str:N #1 _rows_seq }
500             { \int_eval:n {\g_@@_row_int + 1 - ##1 } }
501         }

```

We also have to set the chunk rows to its max value before calling \LTechunk so that we don't get extra increments of the main row counter due to \everycr.

```

502         \int_gset:Nn \LT@rows { \LTchunksize }
503     }

```

If we are still in column zero then we had an empty \endhead and so making any assignment, etc., would start a row — something we don't want. To get out of this trap we run \crrc (which would normally come inside \LTechunk. That will then trigger \everycr and update row counter unnecessarily, but now we have a defined state, so we can use \noalign to undo that. We also change \LT@rows so that further \crs do not do any harm (as explained above).

The \crrc inside \LTechunk will be bypassed in that case as we have just executed a \crrc and are still in scanning modus for \omit or \noalign.

```

504     {
505         \crrc
506         \noalign{

```

.....longtable.sty.....

```
507     \int_step_inline:nn
508         { \LT@rows }
509         {
510             \seq_gput_left:ce
511                 {g_@@\cs_to_str:N #1 _rows_seq }
512                 { \int_eval:n {\g_@@_row_int - ##1 } }
513         }
514     \tbl_gdecr_row_count:           % undo the increment
515     \int_gset:Nn \LT@rows { \LTchunksize }
516 }
517 }
518 \LT@echunk
```

Changed from `\relax` to `\endgraf` at V3.04, see `\LT@start`.

```
519 \ifx\LT@start\endgraf
520     \LT@err
521     {Longtable~ head~ or~ foot~ not~ at~ start~ of~ table}%
522     {Increase~ LTchunksize}%
523 \fi
524 \setbox#1\box\z@
525 \@@_trace:n {-->>~ Saving~\noexpand#1}
526 \LT@get@widths
527 \LT@bchunk}

528 \ExplSyntaxOff
529 (@@=)
```

`\endfirsthead` Call `\LT@end@hd@ft` with the appropriate box.

```
\endhead 530 \def\endfirsthead{\LT@end@hd@ft\LT@firsthead}
\endfoot 531 \def\endhead{\LT@end@hd@ft\LT@head}
\endlastfoot 532 \def\endfoot{\LT@end@hd@ft\LT@foot}
533 \def\endlastfoot{\LT@end@hd@ft\LT@lastfoot}
```

10.13 The `\multicolumn` command

Earlier versions needed a special ‘draft’ form of `\multicolumn`. This is not needed in version 4, and so these commands have been removed.

`\LTmulticolumn`

`\LT@mcwarn`

10.14 Footnotes

The standard `\footnote` command works in a `c` column, but we need to modify the definition in a `p` column to overcome the extra level of boxing. These macros are based on the `array` package, but should be OK for the standard `tabular`.

`\LT@startpbox` Add extra code to switch the definition of `\@footnotetext`.

```
534 \def\LT@startpbox#1{%
535     \bgroup
```

.....longtable.sty.....

```
536 \color@begingroup
537 \let\@footnotetext\LT@p@ftntext
538 \setlength\hspace{#1}%
539 \arrayparboxrestore
540 \everypar{%
541   \vrule \@height \ht\@arstrutbox \@width \z@
542   \everypar{}}%
543 }
```

\LT@endpbox After the parbox is closed, expand `\LT@p@ftn` which will execute a series of `\footnotetext[⟨num⟩]{⟨note⟩}` commands. After being lifted out of the parbox, they can migrate on their own from here.

```
544 \def\LT@endpbox{%
545   \finalstrut\@arstrutbox

546   \color@endgroup
547   \egroup
548   \the\LT@p@ftn
549   \global\LT@p@ftn{}}%
550 \hfil}
```

\LT@p@ftntext Inside the ‘p’ column, just save up the footnote text in a token register.

```
551 \long\def\LT@p@ftntext#1{%
552   \edef\@tempa{\the\LT@p@ftn\noexpand\footnotetext[\the\c@footnote]}}%
553   \global\LT@p@ftn\expandafter{\@tempa{#1}}}%
```

Some variables need for the tagging support.

```
554 <@@=tbl>
555 \ExplSyntaxOn
556   \seq_new:N \g_@@_LT@firsthead_rows_seq
557   \seq_new:N \g_@@_LT@head_rows_seq
558   \seq_new:N \g_@@_LT@lastfoot_rows_seq
559   \seq_new:N \g_@@_LT@foot_rows_seq
560 \ExplSyntaxOff
561 <@@=>
562 </package>
```

.....Page 32.....